

Wall mounted receptacle

Part number: 75448



MENNEKES
Elektrotechnik GmbH & Co. KG

Aloys-Mennekes-Straße 1
57399 Kirchhundem
GERMANY

www.MENNEKES.org

Product Description

- MetalLine
- pre-wired for installation
- contactor and electrical interlock
- highly heat resistant contact carrier, silver plated contacts
- external fixing
- 15° inclination
- cable entry bushing for cables of 20 mm up to 70 mm at top and blind flange at bottom
- enclosure made of sheet steel, painted in RAL 1021
- sea water products are available on request

Technical Details

Wall mounted receptacle - Part No. 75448	75448
Ampere	400A
Number of poles	5p
Clock position	6h
Nominal voltage AC	400V
Nominal frequency	50 - 60 Hz
Protection type IP	IP55
Contact carrier	highly heat resistant contact carrier, silver plated contacts
X-CONTACT	no
Screw drive external screws	hexagon
Pilot contact	2 pilot contacts
Pilot contact switch	no
Contactor	400A 3p
DIN rail	no
Inspection window	no
Enclosure base can be turned 180°	no
Insertion direction	angled
Inclination	15°
Type of mounting	external fixing
Highly resistant to chemicals	no
LED voltage indicator	no
Tightening torque external screws	20 Nm
Conductor cross-section min.	70 mm ²

Wall mounted receptacle - Part No. 75448		75448
Conductor cross-section max.		240 mm ²
Conductor cross-section pilot max.		4 mm ²
IK code		IK07
Weight (net)		45000 g
Packaging unit		1 pcs
Quantity per pallet		2 pcs
EAN / identification number		4015394184720

Permissible ambient conditions		
	Min.	Max.
Permissible ambient temperature	-40 °C	70 °C

Material properties	
Housing	sheet steel yellow [similar RAL 1021]
Front part	aluminium grey [no RAL colour code]
Hinged lid	metal grey [no RAL colour code]
External screws	stainless steel bare

Material resistance	
The material resistance overview can be found on the website in the section "Knowledge" - "Product knowledge" - "Materials".	

Material and environmental properties	
RoHS 2011/65/EU inkl. 2015/863/EU	✓
POP regulation (EU) 2019/1021	✓
Halogen-free	yes

Regulations and Standards


Norm

DIN EN IEC 60309

Declaration of Conformity

CE

Dimensional Drawing



Drawing
1 MB 404/2

Dim. in mm