

Wall mounted receptacle DUO

Part number: 7636



MENNEKES
Elektrotechnik GmbH & Co. KG

Aloys-Mennekes-Straße 1
57399 Kirchhundem
GERMANY

www.MENNEKES.org

Product Description

- pre-wired for installation
- mechanical DUO-interlock
- switch 3p
- external fixing, prepared for internal fixing
- 20° inclination
- receptacles can be locked with a padlock
- highly resistant to chemicals

Technical Details

Wall mounted receptacle DUO - Part No. 7636	7636
Product serie	DUO
Ampere	32A
Number of poles	5p
Clock position	6h
Nominal voltage AC	400V
Nominal frequency	50 - 60 Hz
Protection type IP	IP67
Contact carrier	standard
X-CONTACT	no
Screw drive external screws	allen key, slot
Pilot contact	without pilot contact
Pilot contact switch	no
Load break switch	32A 3p
DIN rail	no
Inspection window	no
Cable entry at the top	2 x M25, 2 x M20
Cable entry at the bottom	2 x M25, 2 x M20
Enclosure base can be turned 180°	no
Insertion direction	angled
Inclination	20°
Type of mounting	external fixing, prepared for internal fixing
Highly resistant to chemicals	yes
LED voltage indicator	no

Wall mounted receptacle DUO - Part No. 7636	7636
Lockable	yes, with a padlock up to max. 8 mm
Conductor cross-section min.	1.5 mm ²
Conductor cross-section max.	10 mm ²
Weight (net)	1720 g
Packaging unit	1 pcs
Quantity per pallet	76 pcs
EAN / identification number	4015394231905

Permissible ambient conditions		
	Min.	Max.
Permissible ambient temperature	-25 °C	40 °C
Average temperature over 24 hours		35 °C

Material properties	
Base	PBT/PC black [similar RAL 9005]
Upper part	PBT/PC light grey [similar RAL 7035]
Hinged lid	PA6 red [similar RAL 3013]
	TPE black [similar RAL 9005]
	PBT/PC squirrel grey [similar RAL 7000]
Rotary handle	PA6 red [similar RAL 3013]
External screws	PA6 light grey [similar RAL 7035]

Material resistance
The material resistance overview can be found on the website in the section “Knowledge” - “Product knowledge” - “Materials”.

Material and environmental properties

RoHS 2011/65/EU inkl. 2015/863/EU

✓

POP regulation (EU) 2019/1021

✓

Halogen-free

no

Regulations and Standards

Norm

DIN EN IEC 60309-4


Declaration of Conformity

CE

Test label

EAC

Dimensional Drawing



Drawing 1 MB 551	Amp. Poles	16			32		
		3	4	5	3	4	5
Dim. in mm	a	225	225	225	225	225	225
	b	168	168	168	168	168	168
	b1	130	130	130	130	130	130
	c	80	80	80	80	80	80
	c1	166	166	166	166	166	166
	c2	182	185	186	197	197	198
	d	204	204	204	204	204	204
	d1	145	145	145	145	145	145
	e	150	150	150	150	150	150
	f	7	7	7	7	7	7
	f1	Ø7	Ø7	Ø7	Ø7	Ø7	Ø7
	g	8	8	8	8	8	8

Cable entries: closed for cut out. 2 x M 25 each on top and bottom, 2 x M 20 each on top and bottom for cut out.